



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

No.: 2021312301002773

Applicant PARKER HANNIFIN MANUFACTURING France SAS
Address 4 boulevard Eiffel, 21604 LONGVIC, France
Manufacturer PARKER HANNIFIN MANUFACTURING France SAS
Address 4 boulevard Eiffel, 21604 LONGVIC, France
Production Factory PARKER HANNIFIN MANUFACTURING France SAS
Production Address 4 boulevard Eiffel, 21604 LONGVIC, France
Product Servomotor
Model/Type EX4*E***1**C
Ex marking Ex db IIB T4 Gb, Ex tb III C T135°C Db
Reference Standards GB/T3836.1-2021, GB/T3836.2-2021, GB/T3836.31-2021

Certification mode Type Test + Initial Factory Inspection + Post-Certification Surveillance

The product(s) is verified and certified according to CNCA-C23-01: 2019 *China Compulsory Certification Implementation Rule on Explosion Protected Electrical Product* and CNEX-C2301-2019 *Guideline of China Compulsory Certification Implementation Rule on Explosion Protected Electrical Product*.

See Annex for the detailed product information (4 pages)

Initial issue date: 2021-02-01

Issued date: 2023-04-19

Valid to: 2026-01-31

The validity of this certificate is maintained through the regular supervision of the issuing authority during the validity period.

Where any discrepancy arises between the English translation and the original Chinese version, the Chinese version shall prevail.

Director:



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co., Ltd.



中国认可
产品
PRODUCT
CNAS C208-P

<http://www.ccc-cnex.com>
ccc.china-ex.com

Add: No. 20, North Zhongjing Road, Nanyang, Henan, P. R. China
Tel: 0377-63239734

P.C.: 473008

Email: ccc@cn-ex.com

CN 0001742



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

(Annex)

No.: 2021312301002773

Page 1 of 4

Product information:

1. This certificate covers the following models:

- EX4*E***1**C

Product code:

Product code:											
Code	EX	4	*	E	*	*	*	1	*	*	C
	1	2	3	4	5	6	7	8	9	10	11
1	Product Series										
2	Motor size			4							
3	Motor length			20, 30							
4	Motor version			E: ATEX/IECEX/CCC motor							
5	Feedback Sensor			A: resolver 2 poles transformation ratio = 0.5 P: DSL encoder singleturn EKS36 – SIL2 Q: DSL encoder multiturn EKM36 – SIL2 R: Hiperface encoder singleturn SKS36 (128pulses) - SIL2 S: Hiperface encoder mutiturn SKM36 (128pulses) - SIL2 T: Hiperface encoder singleturn SRS50 (1024pulses) U: Hiperface encoder mutiturn SRM50 (1024pulses) X: Incremental 2048ppr and with commutation – on request Y: sensorless							

Issued date: 2023-04-19

Director:

穆大玉



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co.,Ltd.



中国认可
产品
PRODUCT
CNAS C208-P



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

(Annex)

No.: 2021312301002773

Page 2 of 4

		Z : Special encoder
6	Torque / Speed Characteristics	A,B... to Z
7	Painting	R: no painting B: Black painting
8	Electric connection	1: Cable gland
9	Break and thermal sensor option	2: Without brake 5: With brake
10	Mechanical Interface	00: IP64 plain shaft 01: IP64 key on shaft 10: IP65 with plain shaft 11: IP65 with key on shaft
11	Nameplate	CCC

Ratings:

Supply voltage of the associated servodrive	24V DC	48V DC	230V AC single-phase/ three-phases	400V AC three-phases
Continuous supply voltage (V)	24±10%	48±10%	310±10%	550±10%
Output frequency (Hz)	0 to 600	0 to 600	0 to 600	0 to 600
Permanent current into one phase (Â/Arms)	17/12 Max	17/12 Max	14/9.8 Max	8/5.6 Max

Issued date: 2023-04-19

Director:

穆大玉



Nanyang Explosion Protected Electrical Apparatus Research Institute Co.,Ltd.



中国认可
产品
PRODUCT
CNAS C208-P

<http://www.ccc-cnex.com>
ccc.china-ex.com

Add: No. 20, North Zhongjing Road, Nanyang, Henan, P. R. China
Tel: 0377-63239734

P.C.: 473008

Email: ccc@cn-ex.com



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

(Annex)

No.: 2021312301002773

Page 3 of 4

Maximum current into one phase (A/Arms)	34/24 Max	34/24 Max	28/19.8 Max	16/11.3 Max
Maximum permanent power of the motor (W)	200 Max	400 Max	3400 Max	3400 Max

Thermo-fuse triggering threshold: 130°C 0/-5°C

Thermo-switch triggering threshold: 125°C ± 5°C

The cable used shall withstand the following temperatures:

With derating of -20% of the Maximum permanent power of the motor				With derating of -55% of the Maximum permanent power of the motor			
Ta=35°C	Ta=39°C	Ta=41°C	Ta=50°C	Ta=45°C	Ta=46°C	Ta=49°C	Ta=60°C
/	/	/	89°C	/	/	/	91°C

Ingress protection: IP64/IP65 is applicable for product with marking Ex db IIB T4 Gb

IP65 is applicable for product with marking Ex tb III C T135°C Db

Ex marking: Ex db IIB T4 Gb, Ex tb III C T135°C Db

- Producers should organize production in accordance with the technical documents approved by the certification body.

2. Specific conditions of safety use:

- Rated ambient temperature range: -20°C~+60°C.
- The gap and length of flameproof joints should be in accordance with those indicated in clause 4.4.3 of instructions.

Issued date: 2023-04-19

Director:



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co.,Ltd.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

(Annex)

No.: 2021312301002773

Page 4 of 4

- The screws used for the assembly of the various parts of explosion-proof enclosures must have a yieldstress higher or equal to: 700MPa.
 - See instruction manual for other information.
3. Certificate related report(s):
- Type test report: CQST2012C029, CQST2012C029/01
 - Factory inspection report: CN2021Q010017
4. Certificate change information:
- 1st change on April 19, 2023:
Updated the standards for certification.

Issued date: 2023-04-19

Director:



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co.,Ltd.



中国认可
产品
PRODUCT
CNAS C208-P