



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

No.: 2021312301002775

Applicant PARKER HANNIFIN MANUFACTURING France SAS
Address 4 boulevard Eiffel, 21604 LONGVIC, France
Manufacturer PARKER HANNIFIN MANUFACTURING France SAS
Address 4 boulevard Eiffel, 21604 LONGVIC, France
Production Factory PARKER HANNIFIN MANUFACTURING France SAS
Production Address 4 boulevard Eiffel, 21604 LONGVIC, France
Product Servomotor
Model/Type EX8*E***1**C
Ex marking Ex db IIB T4 Gb, Ex tb III C T135°C Db
Reference Standards GB/T3836.1-2021, GB/T3836.2-2021, GB/T3836.31-2021

Certification mode Type Test + Initial Factory Inspection + Post-Certification Surveillance

The product(s) is verified and certified according to CNCA-C23-01: 2019 *China Compulsory Certification Implementation Rule on Explosion Protected Electrical Product* and CNEX-C2301-2019 *Guideline of China Compulsory Certification Implementation Rule on Explosion Protected Electrical Product*.

See Annex for the detailed product information (4pages)

Initial issue date: 2021-02-01

Issued date: 2023-04-19

Valid to: 2026-01-31

The validity of this certificate is maintained through the regular supervision of the issuing authority during the validity period.

Where any discrepancy arises between the English translation and the original Chinese version, the Chinese version shall prevail.

Director:



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co., Ltd.



中国认可
产品
PRODUCT
CNAS C208-P

<http://www.ccc-cnex.com>
ccc.china-ex.com

Add: No. 20, North Zhongjing Road, Nanyang, Henan, P. R. China
Tel: 0377-63239734

P.C.: 473008

Email: ccc@cn-ex.com

CN 0001744



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

(Annex)

No.: 2021312301002775

Page 1 of 4

Product information:

1. This certificate covers the following models:

- EX8*E***1**C

Product code:

Product code:											
Code	EX	8	*	E	*	*	*	1	*	*	C
	1	2	3	4	5	6	7	8	9	10	11
1	Product Series										
2	Motor size			8							
3	Motor length			20, 40, 60							
4	Motor version			E: ATEX/IECEX /CCCmotor							
5	Feedback Sensor			A: resolver 2 poles transformation ratio = 0.5 P: DSL encoder singleturn EKS36 – SIL2 Q: DSL encoder multiturn EKM36 – SIL2 R: Hiperface encoder singleturn SKS36 (128pulses) - SIL2 S: Hiperface encoder mutiturn SKM36 (128pulses) - SIL2 T: Hiperface encoder singleturn SRS50 (1024pulses) U: Hiperface encoder mutiturn SRM50 (1024pulses) X: Incremental 2048ppr and with commutation – on request Y: sensorless							

Issued date: 2023-04-19

Director:

穆大玉



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co.,Ltd.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

(Annex)

No.: 2021312301002775

Page 2 of 4

		Z : Special encoder
6	Torque / Speed Characteristics	A,B... to Z
7	Painting	R: no painting B: Black painting
8	Electric connection	1: Cable gland
9	Break and thermal sensor option	2: Without brake 5: With brake
10	Mechanical Interface	00: IP64 plain shaft 01: IP64 key on shaft 10: IP65 with plain shaft 11: IP65 with key on shaft
11	Nameplate	CCC

Ratings:

Supply voltage of the associated servodrive	230V AC single-phase/ three-phases	400V three-phases
Continuous supply voltage (V)	310±10%	550±10%
Output frequency (Hz)	0 to 500	0 to 500
Permanent current into one phase (Â/Arms)	100/70.7 Max	50/35.3 Max
Maximum current into one phase (Â/Arms)	200/141.4 Max	100/70.7 Max
Maximum permanent power of the motor (W)	10000 Max	10000 Max

Issued date: 2023-04-19

Director:

穆大玉



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co.,Ltd.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

(Annex)

No.: 2021312301002775

Page 3 of 4

Thermo-fuse triggering threshold: 130°C 0/-5°C

Thermo-switch triggering threshold: 125°C ± 5°C

The cable used shall withstand the following temperatures:

Without derating of the Maximum permanent power of the motor			With derating of -20% of the Maximum permanent power of the motor				With derating of -55% of the Maximum permanent power of the motor			
Ta=27°C	Ta=32°C	Ta=40°C	Ta=35 °C	Ta=39 °C	Ta=41 °C	Ta=50 °C	Ta=45 °C	Ta=46 °C	Ta=49 °C	Ta=60 °C
/	/	88°C	/	/	82°C	91°C	/	/	83°C	94°C

Ingress protection: IP64/IP65 is applicable for product with marking Ex db IIB T4 Gb

IP65 is applicable for product with marking Ex tb III C T135°C Db

Ex marking: Ex db IIB T4 Gb, Ex tb III C T135°C Db

- Producers should organize production in accordance with the technical documents approved by the certification body.

2. Specific conditions of safety use:

- Rated ambient temperature range: -20°C~+60°C.
- The gap and length of flameproof joints should be in accordance with those indicated in clause 4.4.3 of instructions.
- The screws used for the assembly of the various parts of explosion-proof enclosures must have a yieldstress higher or equal to property class 12.9.
- See instruction manual for other information.

3. Certificate related report(s):

Issued date: 2023-04-19

Director:

穆大玉



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co., Ltd.



中国认可
产品
PRODUCT
CNAS C208-P



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION (Annex)

No.: 2021312301002775

Page 4 of 4

- Type test report: CQST2012C031, CQST2012C031/01
- Factory inspection report: CN2021Q010017
- 4. Certificate change information:
 - 1st change on April 19, 2023:
Updated the standards for certification.

Issued date: 2023-04-19

Director:



Nanyang Explosion Protected Electrical
Apparatus Research Institute Co., Ltd.



中国认可
产品
PRODUCT
CNAS C208-P